

Compact Shaker KS 15 A control



Description

The programmable Orbital Shaker KS 15 A control with touch display for reproducible shaking tasks. The loading capacity is 15 kg on a shaking platform of 400 x 300 mm.

Basic Equipment

Basic device without shaking plate, **without rack system**

With touch display and programmable control.

Loading Capacity

Erlenmeyer flasks 100 ml 20 pieces
Erlenmeyer flasks 250 ml 15 pieces
Erlenmeyer flasks 500 ml 12 pieces
Erlenmeyer flasks 1000 ml 5 pieces
Separating funnels 250 ml 1 pieces

You will find further loading possibilities [here](#)

Options

[USB 2.0 interface](#)

[RS 232 interface](#)

[Control interface](#)

[Safety Package](#)

[Defined stop](#)

Details

Motion: orbital
Shaking platform: 400 x 300 mm
Max. load: 15 kg
Shaking speed: 30 - 420 rpm, in steps of 5
Stroke: 17 mm
Runtime: programmable / continuous
Order No.: 6170 000
Accessory: Rack System Combifix KS
Universal tray KS
Incubator Hood TH 15

Technical specifications

Electrical supply: 230 V or 115 V, 50 / 60 H please indicate in case of order
Enclosure protection: IP 21
Heat emission: approx. 7 W
Ambient temperature: 5°C to 50°C
Relative humidity: ~ 85 %
Dimensions (w x d x h): 510 x 490 x 150 mm
Weight: 19 kg