


Microplate Shaker TiMix 5



Description

The Microplate Shaker TiMix 5 guarantees optimal mixing of small sample volumes in microplates, deepwell-plates or other plates in microplate format. The wide choice of different rack systems allows fastening between 8 and 48 microplates.

Basic Equipment

Basic device without shaking plate, without rack system

Loading Capacity

Standard rack system 0052 101	8 microplates
Rack system with pins 0052 096	8 microplates
Standard rack system 0052 101 + Additional tray 0052 102	16 microplates

RS high clamping pins 0052 104 24 microplates
RS metal clamping pins 0052 125 48 microplates

Details

Motion: exact orbital motion
Shaking platform: 400 x 300 mm for 8 microplates
Max. load: 5 kg
Shaking speed: 100 - 1400 rpm, steplessly adjustable
Stroke: 3 mm
Timer: 0 - 120 min / continuous
Order No.: 6166 000
Accessory: Standard Rack System TiMix 5
Additional tray TiMix 5
Rack System with clamping pins
Rack System with high clamping pins
Rack System with metal clamping pins
Rack System Combifix KS
Universal tray KS
Incubator Hood TH 15

Technical specifications

Electrical supply: 230 V or 115 V, 50 / 60 H please indicate in case of order
Enclosure protection: IP 21
Heat emission: approx. 9 W
Ambient temperature: 5°C to 50°C
Relative humidity: ~ 85 %
Dimensions (w x d x h): 510 x 490 x 150 mm
Weight: 19 kg