

DispensMate

Bottle-Top Dispenser

For safer and more efficient way to handle chemicals

Features

- Excellent chemical resistance, Inert and high strength components made of PTFE, FEP, BSG, PP
- Fully autoclavable at 121°C (only liquid accessible parts)
- Available in 4 dispensing volume ranges from 0.5mL to 50mL
- Easy to disassemble and clean for periodic maintenance
- Supplied with most popular adapters (S40, GL32, GL38, GL25, GL28)

Applications

DLAB bottle-top dispensers offer high precision and accuracy with ISO 8655 conformed calibration for use in areas such as pharmacology, biotechnology, healthcare, food and beverage, chemistry, environmental monitoring and academy&research.

1. Easy-to-use volume adjustment
2. Smooth piston design provides effortless dispensing experience
3. Easy-to-use closure cap protects user from exposure to reagent
4. Adapters to comfortably fit most laboratory reagent bottles

Specifications

Cat. No.	Volume Range	Graduation	Systematic Error		Random Error	
	mL	mL	μL	%	μL	%
7032100101	0.5-5	0.1	±25	±0.5	±10	±0.2
7032100102	1.0-10	0.2	±50	±0.5	±20	±0.2
7032100103	2.5-25	0.5	±125	±0.5	±50	±0.2
7032100104	5.0-50	1.0	±250	±0.5	±100	±0.2



Cat. No.	17400131	17400132	17400133	17400134	17400135	17400037	17400021	17100073	17100553	17100696	17100767
Accessories	GL32, Adapter, 45/32mm	GL38, Adapter, 45/38mm	GL25, Adapter, 32/25mm	GL28, Adapter, 32/28mm	S40, Adapter, 45/40mm	Reagent Bottle (Brown, 1L)	Filling tube (m)	Discharge tube(m)	GL45, adapter, 45mm	Discharge tube combination (adapter 25mL、50mL)	Discharge tube combination (adapter 5mL、10mL)