Coming soon

HB100-Pro

Circular heating block

NEW

Features

- Fast heating: The room temperature rises to 100 °C for less than 10 minutes
- Small size: compact internal structure, smaller footprint
- Accurate temperature control: Temperature control accuracy<1 °C
- Dual display option: set temperature main display, time main display
- Multiple module options: 6 heating modules can be selected, with tightly arranged holes to accommodate more samples
- Compatible containers: 0.2mL, 0.5mL, 1.5mL, 2mL, 5mL



Specifications	HB100-Pro
Temperature display	LED dot matrix screen
Temperature control range [℃]	Room temperature -100 ℃
Temperature display error	±0.5℃
Temperature stability @ 37 ℃	±0.3
Timing range	0-99h59min
Allow relative humidity	＜80%
Input power supply	100-120V，50/60Hz 200-220V，50/60Hz
Dimensions [length x width x height]	210×180×130mm
Weight [kg]	0.9kg

Cat. No.18901479

Circular heating module
（18X5mL）



Cat. No.18901477

Circular heating module
（59X0.5mL）



Cat. No.18901478

Circular heating module
（96X0.2mL）



Cat. No.18901476

Circular heating module
（39X1.5mL）



Cat. No.18901480

Circular heating module
（24X0.5mL+30x1.5mL）



Cat. No.18901704

Circular heating module
（39X2mL）

